



The Partizan PSW-8 v1.0 is a CCTV Ethernet switch featuring eight Power over Ethernet (PoE) ports and two regular ports, equipped to support a total PoE power output of 96.2 watts at 15.4 or 30 watts per port. It operates with a switching capacity of 2 Gbps and adheres to multiple standards, including IEEE 802.3i and IEEE 802.3af. This device functions optimally in operating temperatures ranging from 0 to 40 °C and can withstand humidity levels between 20-95% RH (non-condensing). The unit is constructed with dimensions of 200 (L) x 120 (W) x 45 (H) mm and weighs 600 grams.

| Product details           |  |
|---------------------------|--|
| Model                     | PSW-8  |
| Version                   | v1.0   |
| SKU                       | 1690   |
| Specification             |  |
| Gigabit ethernet ports    | 2 x 100/1000 M   |
| Gigabit PoE ports         | 8 x 100/1000 M   |
| PoE power (per port)      | 15.4 W, 30 W   |
| PoE power (total)         | 96.2 W   |
| Switching capacity        | 2 Gbps   |
| Supported standards       | IEEE 802.3i (10Base-T) , IEEE 802.3af, IEEE 802.3at , IEEE 802.3u (100Base-TX), IEEE 802.3x (Flow control), IEEE 802.3af — DTE Power via MDI |
| Electrical specification  |  |
| AC Plug                   | EU (Type C/F)  |
| AC power supply           | 100-240 V 50/60 Hz   |
| Mechanical specifications |  |
| Dimension                 | 200x120x45 mm  |
| Weight                    | 600 g  |
| Operating conditions      |  |

|                       |                            |
|-----------------------|----------------------------|
| Humidity range        | 20-95% RH (non-condensing) |
| Operating temperature | 0 - 40 °C                  |
| Storage temperature   | -30 - 50 °C                |
| <b>Common</b>         |                            |
| Warranty              | 3 years                    |