



Partizan NVH-3252 is a 32-channel network video recorder from the SH series, supporting IP camera connections with recording capabilities at 8MP, 5MP, and 2MP resolutions at 25fps. The unit features H.264 and H.265 video compression with G711A/G711U audio codecs and two-way audio functionality. Storage configuration includes support for four internal HDDs and one external HDD, each up to 10TB capacity. The recorder provides smart analytics including intrusion detection, line crossing detection, face detection, face recognition, pedestrian detection, and cross counting. Video output is available through dual HDMI ports and VGA, with display resolutions up to 1920×1080. The metal-housed unit with plastic front panel measures 378×326×66mm, weighs 4000g, operates on 12V DC with 5000mA consumption, and functions within -40 to 60°C temperature range.

Product details	
Model	NVH-3252
Version	SH v1.0
SKU	2557
Series	SH series
Encoder	
Maximum cameras	32 pcs
Recording modes (IP)	32x8MP@25 fps, 32x5MP@25 fps, 32x2MP@25 fps
Video codec	H.264, H.265
Audio codec	G711A, G711U
Two-way audio	yes
Graphical user interface	
Display resolution	1920x1080, 1440x900, 1280x1024, 1280x720, 1024x768
Video splitter modes	1, 4, 6, 8, 10, 9, 13, 14, 16, 22, 32, 25, 36, 17, 19
Storage	
Internal HDD	4 x 10 TB
External HDD (eSATA)	1 x 10 TB

HDD storage (important note)	For reliable 24/7 operation, it is strongly recommended to use HDDs specifically designed for video surveillance systems. Hard disk drive is not included in the package.
Network	
Network interfaces	RJ-45 (10/100/1000Base-T)
Network functions	DDNS, IP FILTER, Email, NTP, PPPoE, UPnP, FTP, RTP/RTSP
Default IP address	DHCP
HTTP(s) port	80
Control port	9988
RTSP port	554
RTSP URL	rtsp://LOGIN:PASSWORD@IP:PORT/rtsp/streaming?channel=1&subtype=0
Default credentials	
Default login	admin
Default password	admin
Software	
Smart analytics	Intrusion detection, Line crossing detection, Stationary object detection, Pedestrian Detection, Face detection, Cross counting, Face recognition
Smart analytics (important note)	Smart alarms can only be used with SH-series IP cameras
Cloud abilities	Remote access, Cloud recording, PUSH notifications
Desktop apps	Partizan, Setup Tool
Mobile app	Partizan
Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser usage (important note)	Web browser access requires Partizan SurveillancePluginV2 installation for device setup and live view. Available at www.apps.partizan.global
External interfaces	
Video output	VGA, 2 x HDMI
Audio inputs	1
Audio outputs	1

USB ports	2 x USB 2.0, 1 x USB 3.0
Mechanical specifications	
Front panel material	Plastic
Housing material	Metal
Dimension	378 x 326 x 66 mm
Weight	4000 g
Power	
DC power source	12 V
DC consumption	5000 mA
DC power supply	Included
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-40 - 60 °C
Storage temperature	-40 - 60 °C
Common	
Package contents	Optical mouse, Power adapter
Warranty	3 years